















- IAEA guidebook on non-destructive testing of concrete structures, Vienna 2002;
- ACI 228.1R-03 ACI committee report; in place methods to estimate concrete strength.

VII. Conclusion: limitations and reliability.

Ultrasonic method is a great way to study the homogeneity of the concrete. The procedure is simple; the equipment available on the market is easy to use in the laboratory and on site. With the availability of small portable digital instruments, which are relatively inexpensive and easy to use, ultrasonic testing adds a new dimension to the quality of nondestructive testing of in-situ concrete. Since a large number of variables affect the relationship between the parameters of concrete strength and UPV, its use to evaluate the compressive strength of concrete is not recommended unless correlation tests were performed beforehand.

## REFERENCES

ACI 228.1R-03: ACI committee report; in place methods to estimate concrete strength.

ACI. 1995 ACI Committee 318 Standard Building Code

AIEA: guidebook on non-destructive testing of concrete structures, Vienna 2002;

[Elwardany 2005] : El wardany R., «Caractérisation non destructive des structures en béton au moyen des ondes dispersives de rayleigh et de lam», thèse de doctorat, université Cergy Pontoise, 2005.

[Anderson et al 1981]: Anderson D A, Seals R K., «Pulse velocity as predictor of 28 days strength, ACI J., 78, 116, 1981.

ASTM-C 1383, test method for measuring the P-wave speed and the thickness of concrete using the impact echo method annual book of ASTM standards vol.04.02

ASTM-C 597-0, standard test method for pulse velocity through concrete

[Carino et al. 2003] : Carino NJ, Malhotra VM. Handbook on non-destructive testing of concrete second edition, ASTM standards, 2003.

[Cote 1988] : Cote P., «Tomographies sismiques en génie civil», thèse de doctorat, université Joseph Fourier Grenoble, 1988.

D676-02, standard test method for integrity of concrete deep foundation by ultrasonic crosshole testing.

EN 12504, testing concrete in structure part 4; determination of ultrasonic pulse velocity.

[Garnier et al. 2005] : Garnier V, Chaix JF, Rossat M, Payant C, Corneloup G. « Caractérisation non destructive des bétons par propagation d'ondes ultrasonores». LCN, université de la méditerranée, 19<sup>eme</sup> congrés francais de mecanique marseille, 2009.

[Hassaim 1999] : Hassaim J., «Evaluation de l'état du béton par la technique d'analyse spectrale des ondes de rayleigh», thèse de doctorat, université de Sherbrooke, 1999.



[Hevin 1998] : Hevin G., «Utilisation des ondes de surface pour l'auscultation des structures en génie civil ; application à la caractérisation des fissures de surface», thèse de doctorat, université de Grenoble 1998.

[Hornibrook 1930]: Hornibrook F B., «Application of sonic method to freezing and thawing studies of concrete», ASTM, Bull., 101, 5, 1939.

[Jones 1948]: Jones R., «The application of ultrasonic to the testing of concrete», research, 383, London, 1948.

[Jones 1954]: Jones R., «Testing of concrete by an ultrasonic pulse technique», RILEM int. symp. On non-destructive testing of materials and structures, paris, vol. 1, paper n° A17, janvier 1954.

[Jones 1962]: Jones R., «Non-destructive testing of concrete», Cambridge university press, London, 1962.

[Jones et al 1969]: Jones R, Facaoaru I., «Recommandations for testing concrete by the ultrasonic pulse method», Materials and structures, res. testing (Paris) 2 (19), 275, 1969.

[Kaplan 1959]: Kaplan M F., «The effect of age and water to cement ratio upon the relation between ultrasonic pulse velocity and compressive strength of concrete», mag. Concrete, res., 11(32), 85, 1959.

[Kharat 1997] : Kharat Y., «Auscultation des structures en béton par tomographie

sonique de vitesse d'atténuation», thèse de doctorat, université de Sherbrooke, 1997.

[Leslie et al 1949]: Leslie J R., «Cheesman W J., «Ultrasonic method of studding deterioration and cracking in concrete structures», Structures, ACI J. proceeding, 46 (1), 17, 1949.

[Obert 1939]: Obert L., «Sonic method of determining the modulus of elasticity of building materials under pressure», proceeding ASTM, 39, 987, 1939.

[Powers 1938]: Powers T C., «Measuring young's modulus of elasticity by means of sonic vibrations», proceeding ASTM, B8 (part II), 460, 1938.

[Qixian et al 1996]: Qixian L, Bungey J H., «Using compression wave ultrasonic transducers to reassure the velocity of surface waves and hence determine dynamic modulus of elasticity for concrete construction and building materials», Elsevier, 1996.

[RILEM 1972]: RILEM recommendations NDT, testing of concrete by the ultrasonic pulse method, Paris, 1972.

[Sahebi 1996] : Sahebi M., «Application de la tomographie sonique au diagnostic du béton ; possibilités et limites», maitrise en sciences appliquées, université de Sherbrooke, 1996.

[Sturup et al 1984]: Sturup V R, Vechio R J, Caratin H., «Pulse velocity as a measure of concrete compressive strength», ACI SP

82-11, American concrete institute,  
Farmington hills, MI, 1984.

[Thomson 1940]: Thomson W T.,  
«Measuring changes in physical properties  
of concrete by the dynamic method»,  
proceeding ASTM, 40, 1113, 1940.

[Wu et al 1995]: Wu T, Fang J, Liu G, Kuo  
M., «Determination of elastic constants of  
concrete specimen using transient elastic

waves», the journal the acoustical society,  
1995.

[Zhou et al 1995]: Zhou FP, Lydon F D,  
Barr B., «Effect of coarse aggregate on  
elastic modulus and compressive strength  
of high performance concrete», cement and  
concrete research, Elsevier, 1995.